



1330SE

Micro Scissor Lift

- 13 ft. (4 m) platform height and 19 ft. (6 m) working height
- Fits on most elevators with shortest overall length and low GVW
- 24 in. (60 cm) roll-out deck extension with incremental lock positions
- Direct electric drive for exceptional duty cycle
- 2 person platform with 530 lbs (240 kg) capacity
- Drivable at full height
- Fully proportional lift and drive controls
- Ultra compact design fits into small and tight work areas
- Compact size without compromising generous work area



Lightweight, Micro Slim Scissor with True Slide-Out Deck

Standard Features

Work Area

Roll-out Deck Extension with Incremental Locking Positions
 Standard Full Height Swing Gate
 Lanyard Attachments (2)

Performance

Direct Electric Drive
 Fully Proportional Drive and Lift Controls

Power

24v 85Ah DC Electric Power
 Battery Charge Indicator
 110v Power to Platform

Serviceability

Lubrication-free Scissor Bearings
 Easy Maintenance Access to Mechanical and Electrical Components in a Slide-out Tray
 Logically Grouped Components and Numbered Wiring for Easy Reference

Safety

Dedicated Compartment Protects Electrical and Hydraulic Components
 Emergency Shut-off at Platform and Lower Controls
 Non-skid Metal Deck Construction
 Descent Alarm
 Drive Speed Interlock
 Multi-axis Tilt Sensor
 Scissor Maintenance Lock
 Multiple Disc Brakes

Other Features

Removable Upper Controls
 Voltage-compensating Fully Automatic Battery Charger
 Hour Meter
 Machine Tie Downs
 Non-marking Tires
 All Motion Alarm
 Fork Lift Pockets
 Single 110v Receptacle at Chassis for Common Plug Connection for Battery Charger and Power to Platform

Optional Features

Flashing Beacon (Continuous)
 900w Inverter
 Tool Tray
 2-year Extended Warranty



MEC Aerial Work Platforms

Tel: 559.842.1500 | 1401 S. Madera Avenue, Kerman, CA 93630 | USA
 Toll free: 1.877.MEC LIFT | 1.877.632.5438 | Fax: 559.842.1520
 Email: info@MECawp.com | www.MECawp.com

MEC® is a registered trademark of California Manufacturing & Engineering Co., LLC.

97010 DTD 1117

1330SE	U.S.	Metric
Heights		
Working Height*	19 ft.	6 m
Platform Height	13 ft.	4 m
Stowed Height (Top Guardrail)	74 in.	1.9 m
Stowed Height (Rails Folded)	N/A	N/A
Stowed Height (Platform Floor)	35 in.	.9 m
Guardrail Height	39 in.	1 m
Toeboard Height	6 in.	15 cm
Ground Clearance (Stowed)	2.5 in.	6 cm
Ground Clearance (Elevated)	0.6 in.	1.5 cm
Dimensions		
Length-Stowed (Overall)	58 in.	1.5 m
Length-Stowed (Ladder Removed)	51 in.	1.3 m
Chassis Width	30 in.	76 cm
Platform Length (Extended)	75 in.	1.9 m
Platform Length (Retracted)	51 in.	1.3 m
Roll-Out Deck Length	24 in.	60 cm
Platform Width	27.5 in.	70 cm
Wheelbase	41 in.	1.0 m
Total Lift Capacity	530 lb	240 kg
Personnel Capacity	2	
Roll-Out Deck Capacity	250 lbs	113 kg
Speed		
Raise/Lower Speed	20 s / 20 s	
Drive Speed (Stowed)	2.5 mph	4.0 km/h
Drive Speed (Elevated)	0.5 mph	0.8 km/h
Performance		
Gradeability	25%	
Turning Radius (Inside)	18 in.	.45 m
Weight**	1,900 lbs.	860 kg
Power Source	24 v DC, 85Ah Battery Pack	
Controls	Proportional Drive & Lift Controls	
Tires	9 in.	23 cm

*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height.
 **Weight may vary with certain options or configurations.

Important - MEC scissor lifts must be on a hard level surface while elevated.

Warranty - MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

Meets or exceeds the requirements of ANSI A92.6-2006 and CSA B354.2-01.

Specifications subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.

Distributed by:

