



# 4069ERT 4069RT

## Construction-Grade Electric & Diesel-Powered Scissor Lifts

- 40 ft. (12.2 m) Platform Height
- Standard 4-Wheel Drive with Quad-Trax Traction Control
- 40% Gradeability
- Standard Integrated Sheet Material Rack Designed & Approved by MEC
- Two Full Steps Lower at 51" (1.3 m) Platform Entry Height
- Fully Proportional Drive & Lift Controls
- 48v DC Electric or 24.8 hp (18.5kW) Diesel Power
- 69" (175 cm) Overall Width
- Roll-Out Deck Extension with Incremental Lock Positions
- Patented Powerlift<sup>2</sup> Scissor System
- Optional Outriggers with One-touch Auto Leveling
- Optional Pipe Rack/Sheet Material Clamps



The lowest stowed platform height - including the patented sheet material rack

## Standard Features

### Work Area

Standard Integrated Sheet Material Rack  
 Designed and Approved by the Manufacturer  
 Super-low Platform Entry Height  
 Roll-out Deck Extension with Incremental Locking Positions  
 Standard Swing Gate  
 110V Power to the Platform

### Performance

Standard 4-wheel Drive with Quad-Trax Traction Control  
 Fully Proportional Drive and Lift Controls

### Power

48v 375 Ah (420 Ah Optional) DC Electric or  
 24.8 hp (18.5 kW) Kubota Diesel Power

### Serviceability

Lubrication-free Scissor Bearings  
 Easy Maintenance Access to Mechanical and Electrical  
 Components without Raising Platform or Swinging Out Trays  
 Logically Grouped Components and Numbered Wiring  
 for Easy Reference

### Safety

Dedicated Compartments Protect Electrical and  
 Hydraulic Components  
 Emergency Shut-off at Platform and Lower Controls  
 Non-skid Metal Deck Construction  
 Descent Alarm  
 Drive Speed Interlock  
 Multi-axis Tilt Sensor  
 Multiple Disc Brakes, Manual Brake Release  
 Scissor Maintenance Lock  
 4-wheel Automatic Parking Brake

### Other Features

Industrial-grade Solid-State Battery Charger  
 Fold-down Guardrails  
 Hour Meter  
 Powder Coat Finish  
 Battery Charge Indicator  
 Machine Tie-Downs

## Optional Features

Auto-leveling Outriggers	Lanyard Attachments (6)
Flashing Beacon (Continuous)	Pipe Rack
Automotive Horn	Platform Work Lights
Removable Upper Controls	Non-Marking RT Tires
Air Line to Platform	Foam Filled Tires
All Motion Alarm	Turf Terrain Tires
Batter Charge Indicator	CE Compliant Options
1 or 2 Year Extended Warranty	Australian Compliant Options
	CSA Compliant Options



### MEC Aerial Work Platforms

97004 DTD 1017

Tel: 559.842.1500 | 1401 S. Madera Avenue, Kerman, CA 93630 | USA  
 Toll free: 1.877.MEC LIFT | 1.877.632.5438 | Ph: 559.842.1500  
 Email: info@MECawp.com | www.MECawp.com F: 559.842.1520

Provisional specifications. Manufacturer reserves the right to make changes in pursuit of continuous improvement. MEC® is a registered trademark of California Manufacturing & Engineering. Patent 8,631,902

4069 ERT/RT	U.S.	Metric
<b>Heights</b>		
Working Height*	46 ft.*	14 m*
Platform Height	40 ft.	12.2 m
Stowed Height (Top Guardrail)	98.5 in.	2.5 m
Stowed Height (Rails Folded)	78 in.	1.98 m
Stowed Height (Platform Floor)	51 in.	1.3 m
Guardrail Height	43.5 in.	1.11 m
Toeboard Height	6 in.	15 cm
Ground Clearance	10 in.	25 cm
<b>Dimensions</b>		
Length-Stowed (Overall)	126 in.	3.2 m
Width	69 in.	1.75 m
Platform Length (Extended)	166 in.	4.22 m
Platform Length (Retracted)	118 in.	3 m
Roll-Out Deck Length	48 in.	1.21 m
Platform Width (Outside)	59 in.	1.5 m
Sheet Rack Width	7 in.	18 cm
Wheelbase	94.5 in.	2.4 m
Total Lift Capacity	900 lb.	408 kg
Personnel Capacity	2	
Roll-Out Deck Capacity	250 lbs.	113 kg
Sheet Rack Capacity	300 lbs.	136 kg
<b>Speed</b>		
Drive Speed	ERT= 3.3 mph, RT=3.75 mph   ERT=5.3 km/h, RT=6.0 km/h	
<b>Performance</b>		
Gradeability	40%	
Turning Radius (Inside)	79 in.	2 m
Optional Outrigger Range	10° side to side	
Weight (Approximately**)	11,000 lbs.	4990 kg
4-wheel Multi Disc Brakes	Spring-applied Hydraulically Released	
Power Source	48v DC, 375 Ah Battery Pack   24.8 hp Kubota D1105	
Drive	4-wheel Drive	
Controls	Proportional Drive and Lift Controls	
Tires (RT Tread)	26 in. x 12 in.	66 cm x 33 cm

\*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height.  
 \*\*Including outriggers. Weight may vary with certain options or configurations.

**Important** - MEC scissor lifts must be on a hard level surface while elevated.

**Warranty** - MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

**Meets or exceeds** the requirements of ANSI A92.6-2006 & CSA B354.2-01

**Specifications** subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.

Distributed by: